

BRGTM

for better Insulation



LD-66 ADHESIVE FOR SPINDLE PIN

Manufactured using synthetic rubber, BRG Adhesive LD-66 is designed for use with BRG Spindle & Hanger to provide fast bonding for applications such as fixing of Metal Lath/Strip Mesh onto wall prior to plastering in particular crack-prone areas between concrete and brick/block work; as well as for fastening of fiber-glass wool in hot and cold insulation works. Other applications include the fastening of BRG mesh products.

PRODUCT CODE	SIZE	PACKING
LD-66	200g/tube	50 Tubes/Carton

SAFE USE OF PRODUCT

HAZARD IDENTIFICATION

Signs and Symptoms of Exposure:

1. Eye contact may cause severe eye irritation, redness, tearing and blurred vision.
2. Prolonged or repeated skin contact may cause irritation.
3. Inhalation may cause respiratory system irritation and central nervous depression characterized by headache, dizziness, muscle weakness and fatigue.

PRECAUTIONS FOR SAFE HANDLING AND USE

- Eye Protection (Wear safety glasses with side shields or chemical splash goggles when using this product)
- Skin Protection (Wear rubber gloves for direct handling)
- Hygienic Practices (Wash exposed skin prior to eating or drinking)
- Storage (As product is combustible, avoid flames, sparks or any source of ignition. Store away from high temperatures for best result in usage.)

FIRST AID MEASURES

First Aid Procedures

- If this material contacts the eyes, hold eyelids open and flush immediately with a gentle stream of water for at least 15 minutes. Get medical attention.
- In case of skin contact, clean with rubbing alcohol first, followed immediately by washing affected area with soap and water. Get medical attention if necessary.
- In case of inhalation, remove to fresh uncontaminated air. Get medical attention if necessary.

BENEFITS

Initial bond achievable within 5-10 minutes with maximum strength achieved after 24 hours of curing.

COUNTRY OF ORIGIN AUSTRALIA

INSTALLATION NOTES

1. Ensure surface to be applied is free from dirt/oil before commencement.
2. Apply BRG Adhesive LD-66 sparingly onto perforated base of BRG Spindle and without delay push spindle base onto desired position using twisting motions to ensure even spread of adhesive.
3. Allow 5-10 minutes for initial bond or 24 hours for maximum cure.



Building Resources Group Pte. Ltd.

31 Tuas Ave 8, Singapore 639245
Tel: +65 6861 7091 Fax : +65 6861 7092

BRGTM
for better Insulation